



LOW VOLTAGE CABLES

NA2X2Y



APPLICATION

The NA2X2Y complies with DIN VDE 0276-603 (HD 603) and is designed for fixed installation indoors, in cable ducts, underground, in water, or outdoors. It is primarily used in power plants, industrial facilities, and switching stations as well as local distribution networks - wherever robust cables are needed that can withstand high mechanical stress during installation and operation.

TECHNICAL DATA

SCREEN	No
MAX. PERMISSIBLE CONDUCTOR TEMPERATURE (°C)	90 °C
MAXIMUM SHORT-CIRCUIT TEMPERATURE (°C)	250 °C
MINIMUM LAYING TEMPERATURE (°C)	-20 °C
BENDING RADIUS (MM)	15/12xD mm
CPR CLASS	Fca
FLAME RETARDANT	no
MINIMUM STORAGE TEMPERATURE (°C)	-35 °C
OPERATING TEMPERATURE RANGE (°C)	-35-+90 °C
RATED VOLTAGE (KV)	0.6/1 kV
TEST VOLTAGE (KV)	4 kV



CROSS-SECTIONS/VOLTAGE — 0.6/1 KV

CORES & CROSS-SECTION	COND.	SHAPE	RI [OHM/KM]	WI [MM]	WM [MM]	RBV [MM]	Ø [MM]	G [KG/KM]
1x50	Al	RMV	0.641	1	1.8	12xD	14	232
1x70	Al	RMV	0.443	1.1	1.8	12xD	16	309
1x95	Al	RMV	0.32	1.1	1.8	12xD	18	394
1x120	Al	RMV	0.253	1.2	1.8	12xD	20	479
1x150	Al	RMV	0.206	1.4	1.8	12xD	22	587
1x185	Al	RMV	0.164	1.6	1.8	12xD	24	722
1x240	Al	RMV	0.125	1.7	1.8	12xD	26	908
1x300	Al	RMV	0.1	1.8	1.8	12xD	29	1102
1x400	Al	RMV	0.0078	2	1.9	12xD	32	1398
1x500	Al	RMV	0.065	2.2	2	12xD	36	1763
3x50	Al	SM	0.641	1	1.8	12xD	26	870
3x70	Al	SM	0.443	1.1	1.9	12xD	30	1170
3x95	Al	SM	0.32	1.1	2	12xD	33	1463
3x120	Al	SM	0.253	1.2	2.1	12xD	39	1802
3x150	Al	SM	0.206	1.4	2.3	12xD	41	2184
3x185	Al	SM	0.164	1.6	2.4	12xD	45	2647
3x240	Al	SM	0.125	1.7	2.6	12xD	51	3362
3x70+35	Al	SM	0.268	1.1/0.9	1.9	12xD	32	2828
3x95+50	Al	SM	0.193	1.1/1.0	2.1	12xD	37	3757
3x120+70	Al	SM	0.153	1.2/1.1	2.2	12xD	40	4707
3x150+70	Al	SM	0.124	1.4/1.1	2.3	12xD	45	5675
3x185+95	Al	SM	0.0991	1.6/1.1	2.5	12xD	49	7071
3x240+120	Al	SM	0.0754	1.7/1.2	2.7	12xD	56	9138
4x25	Al	RMV	0.727	0.9	1.8	12xD	25	1391
4x35	Al	RMV	0.524	0.9	1.8	12xD	28	1834
4x50	Al	SM	0.387	1	1.9	12xD	29	2255
4x70	Al	SM	0.268	1.1	2	12xD	33	3158
4x95	Al	SM	0.193	1.1	2.1	12xD	37	4200
4x120	Al	SM	0.153	1.2	2.3	12xD	41	5259

4x150	Al	SM	0.124	1.4	2.4	12xD	46	6439
4x185	Al	SM	0.0991	1.6	2.6	12xD	51	7967
4x240	Al	SM	0.0754	1.7	2.8	12xD	57	10324
5x25	Al	RMV	0.727	0.9	1.8	12xD	27	1676
5x35	Al	RMV	0.524	0.9	1.8	12xD	31	2266
5x50	Al	SM	0.387	1	2	12xD	33	2877
5x70	Al	SM	0.268	1.1	2.1	12xD	38	3979
5x95	Al	SM	0.193	1.1	2.3	12xD	42	5342
5x120	Al	SM	0.153	1.2	2.4	12xD	47	6625