



LOW VOLTAGE CABLES

NAYCWY



APPLICATION

The NAYCWY complies with DIN VDE 0276-603 (HD 603) and is suitable for use in power plants, industrial facilities, switching stations, and local networks. It can be permanently installed - indoors, in cable ducts, outdoors, underground, or in water. Thanks to its concentric conductor, it offers additional protection in case of mechanical damage and enables safe potential equalization.

TECHNICAL DATA

SCREEN	Yes
MAX. PERMISSIBLE CONDUCTOR TEMPERATURE (°C)	70 °C
MAXIMUM SHORT-CIRCUIT TEMPERATURE (°C)	160 °C
MINIMUM LAYING TEMPERATURE (°C)	-5 °C
BENDING RADIUS (MM)	15/12xD mm
CPR CLASS	Eca
FLAME RETARDANT	IEC 60332-1-2
MINIMUM STORAGE TEMPERATURE (°C)	-35 °C
OPERATING TEMPERATURE RANGE (°C)	-35-+70 °C
RATED VOLTAGE (KV)	0.6/1 kV
TEST VOLTAGE (KV)	4 kV



CROSS-SECTIONS/VOLTAGE — 0.6/1 KV

CORES & CROSS-SECTION	COND.	SHAPE	RI [OHM/KM]	WI [MM]	WM [MM]	RBV [MM]	Ø [MM]	G [KG/KM]
3x25/16	Al	RMV	1.2	1.2	1.8	12xD	26	969
3x25/25	Al	RMV	1.2	1.2	1.8	12xD	26	1028
3x35/16	Al	RMV	0.868	1.2	1.8	12xD	28	1173
3x35/16	Al	SM	0.868	1.2	1.8	12xD	26	1034
3x35/35	Al	SM	0.868	1.2	1.8	12xD	26	1139
3x50/25	Al	SM	0.641	1.4	1.9	12xD	29	1309
3x50/50	Al	SM	0.641	1.4	1.9	12xD	29	1441
3x70/35	Al	SM	0.443	1.4	2	12xD	33	1740
3x70/70	Al	SM	0.443	1.4	2	12xD	34	1948
3x95/50	Al	SM	0.32	1.6	2.2	12xD	38	2243
3x95/95	Al	SM	0.32	1.6	2.2	12xD	38	2529
3x120/70	Al	SM	0.253	1.6	2.3	12xD	41	2699
3x120/120	Al	SM	0.253	1.6	2.3	12xD	41	3011
3x150/70	Al	SM	0.206	1.8	2.4	12xD	46	3242
3x150/150	Al	SM	0.206	1.8	2.4	12xD	46	3674
3x185/95	Al	SM	0.164	2	2.6	12xD	50	3925
3x185/185	Al	SM	0.164	2	2.6	12xD	50	4492
3x240/120	Al	SM	0.125	2.2	2.8	12xD	56	5018
4x25/16	Al	RMV	1.2	1.2	1.8	12xD	28	1141
4x35/16	Al	SM	0.868	1.2	1.8	12xD	28	1253
4x50/25	Al	SM	0.641	1.4	2	12xD	33	1691
4x70/35	Al	SM	0.443	1.4	2.1	12xD	36	2125
4x95/50	Al	SM	0.32	1.6	2.3	12xD	41	2760
4x95/95	Al	SM	0.32	1.6	2.3	12xD	42	3047
4x120/70	Al	SM	0.253	1.6	2.4	12xD	46	3407
4x150/70	Al	SM	0.206	1.8	2.6	12xD	51	4062
4x150/120	Al	SM	0.206	1.8	2.6	12xD	51	4297
4x150/150	Al	SM	0.206	1.8	2.6	12xD	51	4455
4x185/95	Al	SM	0.164	2	2.8	12xD	56	4995
4x240/120	Al	SM	0.125	2.2	3	12xD	62	6235

