



# N2XSY

Mittelspannungskabel



## TECHNICAL DATA

<b>Al Foil</b>	No	<b>CE-Conformity</b>	yes
<b>Colour of insulation</b>	uncoloured	<b>Colour of sheath</b>	red or black
<b>Conductive tape below screen</b>	Yes	<b>Conductor</b>	Copper
<b>Copper wire screen and tape</b>	Yes	<b>CPR class</b>	Eca
<b>Insulation</b>	XLPE	<b>Maximal operating conductor temperature (°C)</b>	+90
<b>Maximal short-circuit temperature (°C)</b>	+250	<b>Minimal storage temperature (°C)</b>	-25
<b>Minimal temperature for laying (°C)</b>	-5	<b>Non conducting tape above screen</b>	Yes
<b>Operating temperature range (°C)</b>	-35-+90	<b>Packaging</b>	wooden or metal drums
<b>Sheath</b>	PVC		



**CROSS-SECTION DATA — 6/10 kV**

<b>Voltage</b> 6/10 kV	<b>Test voltage</b> 21 kV	<b>Operating temperature range</b> -35-+90 °C
<b>Conductor temperature (max.)</b> +90 °C	<b>Short-circuit temperature (max.)</b> +250 °C	<b>Minimum laying temperature</b> -5 °C
<b>Minimum storage temperature</b> -25 °C	<b>CPR class</b> Eca	<b>Flame retardant</b> EN 60 332-1-2 / EN 60 332-1-3 / E...

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	WI [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x35/16	Cu	0.22	15.3	0.524	3.4	197	187	5	2.1	360	24	904
1x50/16	Cu	0.24	16.3	0.387	3.4	238	220	7.1	2.1	390	26	1039
1x70/16	Cu	0.28	17.9	0.268	3.4	294	268	10	2.1	405	27	1271
1x95/16	Cu	0.3	19.4	0.193	3.4	358	320	13.6	2.1	435	29	1530
1x120/16	Cu	0.34	20.9	0.153	3.4	413	363	17.1	2.1	450	30	1809
1x150/25	Cu	0.36	22.3	0.124	3.4	468	405	21.4	2.1	480	32	2158
1x185/25	Cu	0.4	23.9	0.099	3.4	535	456	26.4	2.1	495	33	2524
1x240/25	Cu	0.44	26.4	0.075	3.4	631	526	34.3	2.1	540	36	3117
1x300/25	Cu	0.49	28.8	0.06	3.4	722	591	42.9	2.1	570	38	3786
1x400/35	Cu	0.54	31.4	0.047	3.4	827	662	57.2	2.1	615	41	4750
1x500/35	Cu	0.61	34.6	0.037	3.4	949	744	71.4	2.1	660	44	5786



**CROSS-SECTION DATA — 12/20 kV**

<b>Voltage</b> 12/20 kV	<b>Test voltage</b> 42 kV	<b>Operating temperature range</b> -35-+90 °C
<b>Conductor temperature (max.)</b> +90 °C	<b>Short-circuit temperature (max.)</b> +250 °C	<b>Minimum laying temperature</b> -5 °C
<b>Minimum storage temperature</b> -25 °C	<b>CPR class</b> Eca	<b>Flame retardant</b> EN 60 332-1-2

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	WI [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x35/16	Cu	0.16	19.5	0.524	5.5	200	189	5	2.1	435	29	1069
1x50/16	Cu	0.17	20.5	0.387	5.5	239	222	7.1	2.1	450	30	1203
1x70/16	Cu	0.19	22.1	0.268	5.5	297	271	10	2.1	465	31	1447
1x95/16	Cu	0.21	23.6	0.193	5.5	361	323	13.6	2.1	495	33	1718
1x120/16	Cu	0.23	25.1	0.153	5.5	416	367	17.1	2.1	510	34	2007
1x150/25	Cu	0.25	26.5	0.124	5.5	470	409	21.4	2.1	540	36	2364
1x185/25	Cu	0.27	28.1	0.099	5.5	538	461	26.4	2.1	555	37	2744
1x240/25	Cu	0.3	30.6	0.075	5.5	634	532	34.3	2.1	600	40	3352
1x300/25	Cu	0.35	33	0.06	5.5	724	599	42.9	2.1	630	42	4032
1x400/35	Cu	0.36	35.6	0.047	5.5	829	671	57.2	2.1	675	45	4988
1x500/35	Cu	0.43	38.8	0.037	5.5	953	754	71.4	2.1	720	48	6080



**CROSS-SECTION DATA — 18/30 kV**

<b>Voltage</b> 18/30 kV	<b>Test voltage</b> 63 kV	<b>Operating temperature range</b> -35-+90 °C
<b>Conductor temperature (max.)</b> +90 °C	<b>Short-circuit temperature (max.)</b> +250 °C	<b>Minimum laying temperature</b> -5 °C
<b>Minimum storage temperature</b> -25 °C	<b>CPR class</b> Eca	<b>Flame retardant</b> EN 60 332-1-2

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	WI [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x50/16	Cu	0.13	25.5	0.387	8	241	225	7.1	2.1	525	35	1439
1x70/16	Cu	0.15	27.1	0.268	8	299	274	10	2.1	540	36	1697
1x95/16	Cu	0.16	28.6	0.193	8	363	327	13.6	2.1	570	38	1979
1x120/16	Cu	0.17	30.1	0.153	8	418	371	17.1	2.1	585	39	2279
1x150/25	Cu	0.19	31.5	0.124	8	472	414	21.4	2.1	615	41	2648
1x185/25	Cu	0.2	33.1	0.099	8	539	466	26.4	2.1	630	42	3036
1x240/25	Cu	0.22	35.6	0.075	8	635	539	34.3	2.1	675	45	3661
1x300/25	Cu	0.24	38	0.06	8	725	606	42.9	2.1	705	47	4368
1x400/35	Cu	0.26	40.6	0.047	8	831	680	57.2	2.1	750	50	5347
1x500/35	Cu	0.29	43.8	0.037	8	953	765	71.4	2.4	795	53	6472