



# NA2XS(F)2Y

Mittelspannungskabel



## TECHNICAL DATA

<b>Al Foil</b>	No	<b>CE-Conformity</b>	yes
<b>Colour of insulation</b>	uncoloured	<b>Colour of sheath</b>	black
<b>Conductive tape below screen</b>	Yes	<b>Conductor</b>	Aluminum
<b>Copper wire screen and tape</b>	Yes	<b>CPR class</b>	Fca
<b>Flame retardant</b>	no	<b>Insulation</b>	XLPE
<b>Maximal operating conductor temperature (°C)</b>	+90	<b>Maximal short-circuit temperature (°C)</b>	+250
<b>Minimal storage temperature (°C)</b>	-35	<b>Minimal temperature for laying (°C)</b>	-20
<b>Non conducting tape above screen</b>	Yes	<b>Operating temperature range (°C)</b>	-35-+90
<b>Packaging</b>	wooden or metal drums	<b>Sheath</b>	PE



### CROSS-SECTION DATA — 6/10 kV

<b>Voltage</b> 6/10 kV	<b>Test voltage</b> 21 kV	<b>Operating temperature range</b> -35-+90 °C
<b>Conductor temperature (max.)</b> +90 °C	<b>Short-circuit temperature (max.)</b> +250 °C	<b>Minimum laying temperature</b> -20 °C
<b>Minimum storage temperature</b> -35 °C	<b>CPR class</b> Fca	<b>Flame retardant</b> no

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	WI [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x50/16	Al	0.24	16.4	0.641	3.4	183	171	4.7	2.1	375	25	625
1x70/16	Al	0.28	17.9	0.443	3.4	228	208	6.6	2.1	390	26	707
1x95/16	Al	0.31	19.4	0.32	3.4	278	248	9	2.1	420	28	808
1x120/16	Al	0.34	20.9	0.253	3.4	321	283	11.3	2.1	435	29	909
1x150/25	Al	0.36	22.3	0.206	3.4	364	315	14.2	2.1	450	30	1089
1x185/25	Al	0.4	23.9	0.164	3.4	418	357	17.5	2.1	480	32	1232
1x240/25	Al	0.44	26.2	0.125	3.4	494	413	22.7	2.1	510	34	1427
1x300/25	Al	0.48	28.3	0.1	3.4	568	466	28.4	2.1	555	37	1666
1x400/35	Al	0.54	31.4	0.0778	3.4	660	529	37.8	2.1	600	40	2089
1x500/35	Al	0.61	34.6	0.0605	3.4	767	602	47.3	2.1	645	43	2456
1x630/35	Al	0.67	38	0.0469	3.4	855	688	59.6	2.1	690	46	2909
1x800/35	Al	0.76	42.3	0.0367	3.4	968	764	75.6	2.4	765	51	3521
1x1000/35	Al	0.84	46.2	0.0291	3.4	1187	852	94	2.4	825	55	4195



### CROSS-SECTION DATA — 12/20 kV

<b>Voltage</b> 12/20 kV	<b>Test voltage</b> 42 kV	<b>Operating temperature range</b> -35-+90 °C
<b>Conductor temperature (max.)</b> +90 °C	<b>Short-circuit temperature (max.)</b> +250 °C	<b>Minimum laying temperature</b> -20 °C
<b>Minimum storage temperature</b> -35 °C	<b>CPR class</b> Fca	<b>Flame retardant</b> no

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	WI [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x50/16	Al	0.17	20.5	0.641	5.5	185	172	4.7	2.1	435	29	780
1x70/16	Al	0.19	22	0.443	5.5	231	210	6.6	2.1	450	30	873
1x95/16	Al	0.21	23.5	0.32	5.5	280	251	9	2.1	480	32	984
1x120/16	Al	0.23	25	0.253	5.5	323	285	11.3	2.1	495	33	1093
1x150/25	Al	0.25	26.4	0.206	5.5	366	319	14.2	2.1	525	35	1282
1x185/25	Al	0.27	28	0.164	5.5	420	361	17.5	2.1	540	36	1434
1x240/25	Al	0.3	30.3	0.125	5.5	496	417	22.7	2.1	585	39	1647
1x300/25	Al	0.32	32.4	0.1	5.5	569	471	28.4	2.1	615	41	1869
1x400/35	Al	0.36	35.5	0.0778	5.5	660	535	37.8	2.1	660	44	2321
1x500/35	Al	0.4	38.7	0.0605	5.5	766	609	47.3	2.1	705	47	2728
1x630/35	Al	0.44	42.1	0.0469	5.5	861	690	59.6	2.4	765	51	3227
1x800/35	Al	0.49	46.4	0.0367	5.5	976	764	75.6	2.4	825	55	3846
1x1000/35	Al	0.54	50.3	0.0291	5.5	1095	837	94.6	2.4	900	60	4634



### CROSS-SECTION DATA — 18/30 kV

<b>Voltage</b> 18/30 kV	<b>Test voltage</b> 63 kV	<b>Operating temperature range</b> -35-+90 °C
<b>Conductor temperature (max.)</b> +90 °C	<b>Short-circuit temperature (max.)</b> +250 °C	<b>Minimum laying temperature</b> -20 °C
<b>Minimum storage temperature</b> -35 °C	<b>CPR class</b> Fca	<b>Flame retardant</b> no

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	WI [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x50/16	Al	0.13	25.5	0.641	8	187	174	4.7	2.1	510	34	988
1x70/16	Al	0.15	27	0.443	8	232	213	6.6	2.1	525	35	1094
1x95/16	Al	0.16	28.5	0.32	8	282	254	9	2.1	555	37	1216
1x120/16	Al	0.17	30	0.253	8	325	289	11.3	2.1	570	38	1335
1x150/25	Al	0.19	31.4	0.206	8	367	322	14.2	2.1	600	40	1535
1x185/25	Al	0.2	33	0.164	8	421	364	17.5	2.1	615	41	1699
1x240/25	Al	0.22	35.3	0.125	8	496	422	22.7	2.1	660	44	1928
1x300/25	Al	0.24	37.4	0.1	8	568	476	28.4	2.1	690	46	2167
1x400/35	Al	0.26	40.5	0.0778	8	659	541	37.8	2.1	735	49	2654
1x500/35	Al	0.29	43.7	0.0605	8	764	616	47.3	2.4	780	52	3087
1x630/35	Al	0.32	47.1	0.0469	8	866	692	59.6	2.4	840	56	3603
1x800/35	Al	0.36	51.4	0.0367	8	984	770	75.6	2.4	900	60	4284
1x1000/35	Al	0.39	55.3	0.0291	8	1095	841	94.6	2.4	975	65	5093