



NA2X2Y

Low Voltage Cables



DESCRIPTION

The NA2X2Y cable is a durable low-voltage cable with an aluminium conductor, PE insulation, and an HDPE sheath. It has been developed for fixed installations under increased mechanical stress and is particularly suitable for demanding industrial and energy infrastructure applications.

TECHNICAL DATA

Bending radius (mm)	15/12xD	Colour of insulation	HD 308 S2
Colour of sheath	black	Conductor	AL
CPR class	Fca	CUScreen	No
Insulation	XLPE	Maximal operating conductor temperature (°C)	90
Maximal short-circuit temperature (°C)	250	Minimal storage temperature (°C)	-35
Minimal temperature for laying (°C)	-20	Operating temperature range (°C)	-35-+90
Packaging	cable drums	Rated voltage (kV)	0.6/1
RoHS/REACH	yes/yes	Self-extinguishing of single cable	no
Sheath	PE	Test voltage (kV)	4



NA2X2Y

CROSS-SECTION DATA — 0.6/1 kV		
Voltage 0.6/1 kV	Test voltage 4 kV	Operating temperature range -35+90 °C
Conductor temperature (max.) 90 °C	Short-circuit temperature (max.) 250 °C	Minimum laying temperature -20 °C
Minimum storage temperature -35 °C	CPR class Fca	Flame retardant no

Designation	Cond.	DI [mm]	RI [Ohm/km]	Wi [mm]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x16	Al	~6.4	1.91	0.7	1.8	12xD	10	104
1x25	Al	~8.4	1.2	0.9	1.8	12xD	12	144
1x35	Al	~9.4	0.868	0.9	1.8	12xD	13	179
1x50	Al	~10.4	0.641	1	1.8	12xD	14	232
1x70	Al	~12.4	0.443	1.1	1.8	12xD	16	309
1x95	Al	~14.4	0.32	1.1	1.8	12xD	18	394
1x120	Al	~16.4	0.253	1.2	1.8	12xD	20	479
1x150	Al	~18.4	0.206	1.4	1.8	12xD	22	587
1x185	Al	~20.4	0.164	1.6	1.8	12xD	24	722
1x240	Al	~22.4	0.125	1.7	1.8	12xD	26	908
1x300	Al	~25.4	0.1	1.8	1.8	12xD	29	1102
1x400	Al	~28.2	0.0078	2	1.9	12xD	32	1398
1x500	Al	~32	0.065	2.2	2	12xD	36	1763
3x16	Al	~15.4	1.91	0.7	1.8	12xD	19	454
3x25	Al	~18.4	1.2	0.9	1.8	12xD	22	634
3x35	Al	~21.4	0.868	0.9	1.8	12xD	25	788
3x50	Al	~22.4	0.641	1	1.8	12xD	26	870
3x70	Al	~26.2	0.443	1.1	1.9	12xD	30	1170
3x95	Al	~29	0.32	1.1	2	12xD	33	1463
3x120	Al	~34.8	0.253	1.2	2.1	12xD	39	1802
3x150	Al	~36.4	0.206	1.4	2.3	12xD	41	2184
3x185	Al	~40.2	0.164	1.6	2.4	12xD	45	2647
3x240	Al	~45.8	0.125	1.7	2.6	12xD	51	3362
3x35+16	Al	~21.4	0.868	0.9/0.7	1.8	12xD	25	855
3x70+35	Al	~28.2	0.268	1.1/0.9	1.9	12xD	32	2828



NA2X2Y

Designation	Cond.	DI [mm]	RI [Ohm/km]	Wi [mm]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
3x95+50	Al	~32.8	0.193	1.1/1.0	2.1	12xD	37	3757
3x120+70	Al	~35.6	0.153	1.2/1.1	2.2	12xD	40	4707
3x150+70	Al	~40.4	0.124	1.4/1.1	2.3	12xD	45	5675
3x185+95	Al	~44	0.0991	1.6/1.1	2.5	12xD	49	7071
3x240+120	Al	~50.6	0.0754	1.7/1.2	2.7	12xD	56	9138
4x10	Al	~14.4	1.83	0.7	1.8	12xD	18	642
4x16	Al	~17.4	1.15	0.7	1.8	12xD	21	910
4x25	Al	~21.4	0.727	0.9	1.8	12xD	25	1391
4x35	Al	~24.4	0.524	0.9	1.8	12xD	28	1834
4x50	Al	~25.2	0.387	1	1.9	12xD	29	2255
4x70	Al	~29	0.268	1.1	2	12xD	33	3158
4x95	Al	~32.8	0.193	1.1	2.1	12xD	37	4200
4x120	Al	~36.4	0.153	1.2	2.3	12xD	41	5259
4x150	Al	~41.2	0.124	1.4	2.4	12xD	46	6439
4x185	Al	~45.8	0.0991	1.6	2.6	12xD	51	7967
4x240	Al	~51.4	0.0754	1.7	2.8	12xD	57	10324
5x10	Al	~16.4	1.83	0.7	1.8	12xD	20	767
5x16	Al	~18.4	1.15	0.7	1.8	12xD	22	1100
5x25	Al	~23.4	0.727	0.9	1.8	12xD	27	1676
5x35	Al	~27.4	0.524	0.9	1.8	12xD	31	2266
5x50	Al	~29	0.387	1	2	12xD	33	2877
5x70	Al	~33.8	0.268	1.1	2.1	12xD	38	3979
5x95	Al	~37.4	0.193	1.1	2.3	12xD	42	5342
5x120	Al	~42.2	0.153	1.2	2.4	12xD	47	6625