



NA2X(F)KLD2Y

High Voltage Cables

No image available

DESCRIPTION

The NA2X(F)KLD2Y high-voltage cable series is designed for industrial applications requiring high voltage class and robust performance, featuring copper conductors and XLPE insulation suitable for direct burial and cable tray installations.

TECHNICAL DATA

Rated voltage (kV)

64/110 kV



CROSS-SECTION DATA — 64/110 kV

Voltage

64/110 kV

Cores & cross-section	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x240RM	0.16	16.5	2.1	86	5510
1x300RM	0.13	15.5	2.2	86	5630
1x400RM	0.1	14.5	2.2	87	5750
1x500RM	0.08	14	2.3	90	6380
1x630RM	0.06	14	2.4	94	7000
1x800RM	0.05	14	2.5	98	7960
1x1000RM	0.04	14	2.6	103	9030
1x1200RMS	0.03	14	2.8	112	10450
1x1400RMS	0.03	14	2.8	114	11190
1x1600RMS	0.02	14	2.9	118	12140
1x1800RMS	0.02	14	3.1	122	13220
1x2000RMS	0.02	14	3.1	124	13900
1x2500RMS	0.02	14.5	3.3	133	15970
1x3000RMS	0.01	14.5	3.5	141	18720