



NA2X(F)KLD2Y

High Voltage Cables

No image available

DESCRIPTION

The NA2X(F)KLD2Y high-voltage cable series is designed for industrial applications requiring high voltage class and robust performance, featuring copper conductors and XLPE insulation suitable for direct burial and cable tray installations.

TECHNICAL DATA

Rated voltage (kV)	64/110 kV
--------------------	-----------


CROSS-SECTION DATA — 64/110 kV

Cores & CS	Cond.	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1×240RM	Al	0.16	16.5	2.1	86	5510
1×300RM	Al	0.13	15.5	2.2	86	5630
1×400RM	Al	0.1	14.5	2.2	87	5750
1×500RM	Al	0.08	14	2.3	90	6380
1×630RM	Al	0.06	14	2.4	94	7000
1×800RM	Al	0.05	14	2.5	98	7960
1×1000RM	Al	0.04	14	2.6	103	9030
1×1200RMS	Al	0.03	14	2.8	112	10450
1×1400RMS	Al	0.03	14	2.8	114	11190
1×1600RMS	Al	0.02	14	2.9	118	12140
1×1800RMS	Al	0.02	14	3.1	122	13220
1×2000RMS	Al	0.02	14	3.1	124	13900
1×2500RMS	Al	0.02	14.5	3.3	133	15970
1×3000RMS	Al	0.01	14.5	3.5	141	18720