



NA2X(F)K2Y

Hochspannungskabel

No image available

TECHNICAL DATA

Conductor Aluminum	Insulation XLPE
Norm Acc. VDE 0276-632	Rated voltage (kV) 64/110
Sheath PE	

CROSS-SECTION DATA — 64/110 kV

Voltage
64/110 kV

Designation	Cond.	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x150RM	Al	0.26	18	1300	67	7360
1x185RM	Al	0.21	17	1300	66	7270
1x240RM	Al	0.16	16.5	1300	67	7480
1x300RM	Al	0.13	15.5	1300	67	7600
1x400RM	Al	0.1	14.5	1400	68	7890
1x500RM	Al	0.08	14	1400	70	8400
1x630RM	Al	0.06	14	1500	74	9390
1x800RM	Al	0.05	14	1600	78	10350
1x1000RM	Al	0.04	14	1700	84	11620
1x1200RMS	Al	0.03	14	1800	91	13250
1x1400RMS	Al	0.03	14	1900	93	14100
1x1600RMS	Al	0.02	14	1900	97	15160
1x1800RMS	Al	0.02	14	2000	101	16410
1x2000RMS	Al	0.02	14	2100	103	17160



NA2X(F)K2Y

Designation	Cond.	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x2500RMS	Al	0.02	14.5	2200	110	19420
1x3000RMS	Al	0.01	14.5	2400	119	22550