



N2X2Y

Niederspannungskabel

No image available

TECHNICAL DATA

Bending radius (mm)	Colour of insulation
15/12xD	HD 308 S2
Colour of sheath	Conductor
black	CU
CPR class	CUScreen
Fca	No
Insulation	Maximal operating conductor temperature (°C)
XLPE	90
Maximal short-circuit temperature (°C)	Minimal storage temperature (°C)
250	-35
Minimal temperature for laying (°C)	Operating temperature range (°C)
-20	-35-+90
Packaging	Rated voltage (kV)
cable drums	0.6/1
RoHS/REACH	Self-extinguishing of single cable
yes/yes	no
Sheath	Test voltage (kV)
PE	4



N2X2Y

CROSS-SECTION DATA — 0.6/1 kV

Voltage 0.6/1 kV	Test voltage 4 kV	Operating temperature range -35-+90 °C
Conductor temperature (max.) 90 °C	Short-circuit temperature (max.) 250 °C	Minimum laying temperature -20 °C
Minimum storage temperature -35 °C	CPR class Fca	Flame retardant no

Designation	Cond.	DI [mm]	RI [Ohm/km]	Wi [mm]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x10	Cu	~5.4	1.83	0.7	1.8	12xD	9	141
1x16	Cu	~6.4	1.15	0.7	1.8	12xD	10	200
1x25	Cu	~8.4	0.727	0.9	1.8	12xD	12	301
1x35	Cu	~9.4	0.524	0.9	1.8	12xD	13	397
1x50	Cu	~10.4	0.387	1	1.8	12xD	14	520
1x70	Cu	~12.4	0.268	1.1	1.8	12xD	16	725
1x95	Cu	~14.4	0.193	1.1	1.8	12xD	18	972
1x120	Cu	~16.4	0.153	1.2	1.8	12xD	20	1207
1x150	Cu	~18.4	0.124	1.4	1.8	12xD	22	1488
1x240	Cu	~22.4	0.0991	1.7	1.8	12xD	26	2388
1x300	Cu	~25.4	0.0601	1.8	1.8	12xD	29	2964
1x400	Cu	~28.2	0.047	2	1.9	12xD	32	3772
1x500	Cu	~32	0.0366	2.2	2	12xD	36	4808
3x10	Cu	~13.4	1.83	0.7	1.8	12xD	17	529
3x16	Cu	~15.4	1.15	0.7	1.8	12xD	19	741
3x25	Cu	~19.4	0.727	0.9	1.8	12xD	23	1122
3x35	Cu	~22.4	0.524	0.9	1.8	12xD	26	1473
3x50	Cu	~22.4	0.387	1	1.8	12xD	26	1729
3x70	Cu	~26.2	0.268	1.1	1.9	12xD	30	2414
3x95	Cu	~29	0.193	1.1	2	12xD	33	3210
3x120	Cu	~32.8	0.153	1.2	2.1	12xD	37	3962
3x150	Cu	~36.4	0.124	1.4	2.3	12xD	41	4906
3x185	Cu	~40.2	0.0991	1.6	2.4	12xD	45	6047
3x240	Cu	~45.8	0.0754	1.7	2.6	12xD	51	7833
3x35+16	Cu	~22.4	0.524	0.9/0.7	1.8	12xD	26	1652
3x50+25	Cu	~25.4	0.387	1.0/0.9	1.8	12xD	29	2075
3x70+35	Cu	~28.2	0.268	1.1/0.9	1.9	12xD	32	2828
3x95+50	Cu	~32.8	0.193	1.1/1.0	2.1	12xD	37	3757
3x120+70	Cu	~35.6	0.153	1.2/1.1	2.2	12xD	40	4707



N2X2Y

Designation	Cond.	DI [mm]	RI [Ohm/km]	Wi [mm]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
3x150+70	Cu	~40.4	0.124	1.4/1.1	2.3	12xD	45	5675
3x185+95	Cu	~44	0.0991	1.6/1.1	2.5	12xD	49	7071
3x240+120	Cu	~50.6	0.0754	1.7/1.2	2.7	12xD	56	9138
4x10	Cu	~14.4	1.83	0.7	1.8	12xD	18	642
4x16	Cu	~17.4	1.15	0.7	1.8	12xD	21	910
4x25	Cu	~21.4	0.727	0.9	1.8	12xD	25	1391
4x35	Cu	~24.4	0.524	0.9	1.8	12xD	28	1834
4x50	Cu	~25.2	0.387	1	1.9	12xD	29	2255
4x70	Cu	~29	0.268	1.1	2	12xD	33	3158
4x95	Cu	~32.8	0.193	1.1	2.1	12xD	37	4200
4x120	Cu	~36.4	0.153	1.2	2.3	12xD	41	5259
4x150	Cu	~41.2	0.124	1.4	2.4	12xD	46	6439
4x185	Cu	~45.8	0.0991	1.6	2.6	12xD	51	7967
4x240	Cu	~51.4	0.0754	1.7	2.8	12xD	57	10324
5x10	Cu	~16.4	1.83	0.7	1.8	12xD	20	767
5x16	Cu	~18.4	1.15	0.7	1.8	12xD	22	1100
5x25	Cu	~23.4	0.727	0.9	1.8	12xD	27	1676
5x35	Cu	~27.4	0.524	0.9	1.8	12xD	31	2266
5x50	Cu	~29	0.387	1	2	12xD	33	2877
5x70	Cu	~33.8	0.268	1.1	2.1	12xD	38	3979
5x95	Cu	~37.4	0.193	1.1	2.3	12xD	42	5342
5x120	Cu	~42.2	0.153	1.2	2.4	12xD	47	6625