



N2X(F)K2Y

Hochspannungskabel

Kein Bild verfügbar

TECHNISCHE DATEN

Isolierung	Leiter
XLPE	Copper
Mantel	Nennspannung (kV)
PE	64/110
Norm	
Acc. VDE 0276-632	

QUERSCHNITTSDATEN — 64/110 kV

Spannung
64/110 kV

Bezeichnung	Leiter	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1×150RM	Cu	0,16	18	1400	67	8300
1×185RM	Cu	0,13	17	1300	66	8400
1×240RM	Cu	0,1	16,5	1400	67	9030
1×300RM	Cu	0,08	15,5	1400	67	9540
1×400RM	Cu	0,06	14,5	1400	69	10410
1×500RM	Cu	0,05	14	1400	71	11590
1×630RM	Cu	0,04	14	1500	75	13470
1×800RM	Cu	0,03	14	1600	80	15590
1×1000RM	Cu	0,03	14	1700	84	17980
1×1200RMS	Cu	0,02	14	1800	89	20530
1×1400RMS	Cu	0,02	14	1900	94	22780
1×1600RMS	Cu	0,02	14	2000	98	25280
1×1800RMS	Cu	0,02	14	2000	102	27940



N2X(F)K2Y

Bezeichnung	Leiter	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1×2000RMS	Cu	0,02	14	2100	103	29610
1×2500RMS	Cu	0,01	14,5	2200	112	35400
1×3000RMS	Cu	0,01	14,5	2400	121	42420