



N2XS(FL)2Y

Mittelspannungskabel

No image available

TECHNICAL DATA

Al Foil Yes	CE-Conformity yes
Colour of insulation uncoloured	Colour of sheath black
Conductive tape below screen Yes	Conductor Copper
Copper wire screen and tape Yes	CPR class Fca
Flame retardant no	Insulation XLPE
Maximal operating conductor temperature (°C) +90	Maximal short-circuit temperature (°C) +250
Minimal storage temperature (°C) -35	Minimal temperature for laying (°C) -20
Non conducting tape above screen Yes	Packaging wooden or metal drums
Sheath PE	

CROSS-SECTION DATA — 6/10 kV

Voltage 6/10 kV	Test voltage 21 kV	Operating temperature range -35-+90 °C
Conductor temperature (max.) +90 °C	Short-circuit temperature (max.) +250 °C	Minimum laying temperature -20 °C
Minimum storage temperature -35 °C	CPR class Fca	Flame retardant no



N2XS(FL)2Y

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	Wi [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x50/16	Cu	0.24	16.3	0.387	3.4	238	220	7.1	2.1	520	26	1010
1x70/16	Cu	0.28	17.9	0.268	3.4	294	268	10	2.1	560	28	1238
1x95/16	Cu	0.3	19.4	0.193	3.4	358	320	13.6	2.1	580	29	1495
1x120/16	Cu	0.34	20.9	0.153	3.4	413	363	17.1	2.1	620	31	1773
1x150/25	Cu	0.36	22.3	0.124	3.4	468	405	21.4	2.1	640	32	2119
1x185/25	Cu	0.4	23.9	0.099	3.4	535	456	26.4	2.1	680	34	2483
1x240/25	Cu	0.44	26.4	0.075	3.4	631	526	34.3	2.1	720	36	3073
1x300/25	Cu	0.48	28.8	0.06	3.4	722	591	42.9	2.1	780	39	3737
1x400/35	Cu	0.54	31.4	0.047	3.4	827	662	57.2	2.1	840	42	4697
1x500/35	Cu	0.61	34.6	0.037	3.4	949	744	71.4	2.1	880	44	5729

CROSS-SECTION DATA — 12/20 kV

Voltage 12/20 kV	Test voltage 42 kV	Operating temperature range -35 - + 90 / -35 - +90 °C
Conductor temperature (max.) +90 °C	Short-circuit temperature (max.) +250 °C	Minimum laying temperature -20 °C
Minimum storage temperature -35 °C	CPR class Fca	Flame retardant no

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	Wi [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x50/16	Cu	0.17	20.5	0.387	5.5	239	222	7.1	2.1	600	30	1166
1x70/16	Cu	0.19	22.1	0.268	5.5	297	271	10	2.1	640	32	1409
1x95/16	Cu	0.21	23.6	0.193	5.5	361	323	13.6	2.1	660	33	1675
1x120/16	Cu	0.23	25.1	0.153	5.5	416	367	17.1	2.1	700	35	1968
1x150/25	Cu	0.25	26.5	0.124	5.5	470	409	21.4	2.1	720	36	2320
1x185/25	Cu	0.27	28.1	0.099	5.5	538	461	26.4	2.1	760	38	2697
1x240/25	Cu	0.3	30.6	0.075	5.5	634	532	34.3	2.1	800	40	3303
1x300/25	Cu	0.32	33	0.06	5.5	724	599	42.9	2.1	860	43	3978
1x400/35	Cu	0.36	35.6	0.047	5.5	829	671	57.2	2.1	900	45	4925
1x500/35	Cu	0.4	38.8	0.037	5.5	953	754	71.4	2.1	980	49	6006



N2XS(FL)2Y

CROSS-SECTION DATA — 18/30 kV

Voltage 18/30 kV	Test voltage 63 kV	Operating temperature range -35+90 °C
Conductor temperature (max.) +90 °C	Short-circuit temperature (max.) +250 °C	Minimum laying temperature -20 °C
Minimum storage temperature -35 °C	CPR class Fca	Flame retardant no

Designation	Cond.	C [uF/km]	DI [mm]	RI [Ohm/km]	Wi [mm]	Ibl [A]	Ibe [A]	Ik [kA]	Wm [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1x50/16	Cu	0.13	25.5	0.387	8	241	225	7.1	2.1	700	35	1405
1x70/16	Cu	0.15	27.1	0.268	8	299	274	10	2.1	740	37	1646
1x95/16	Cu	0.16	28.6	0.193	8	363	327	13.6	2.1	760	38	1926
1x120/16	Cu	0.17	30.1	0.153	8	418	371	17.1	2.1	800	40	2227
1x150/25	Cu	0.19	31.5	0.124	8	472	414	21.4	2.1	820	41	2590
1x185/25	Cu	0.2	33.1	0.099	8	539	466	26.4	2.1	860	43	2975
1x240/25	Cu	0.22	35.6	0.075	8	635	539	34.3	2.1	900	45	3594
1x300/25	Cu	0.24	38	0.06	8	725	606	42.9	2.1	960	48	4300
1x400/35	Cu	0.26	40.6	0.047	8	831	680	57.2	2.1	1020	51	5290
1x500/35	Cu	0.29	43.8	0.037	8	953	765	71.4	2.4	1080	54	6403