



NA2X(F)K2Y

Hochspannungskabel

Kein Bild verfügbar

TECHNISCHE DATEN

Isolierung	Leiter
XLPE	Aluminum
Mantel	Nennspannung (kV)
PE	64/110
Norm	
Acc. VDE 0276-632	

QUERSCHNITTSDATEN — 64/110 kV

Spannung
64/110 kV

Bezeichnung	Leiter	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1×150RM	Al	0,26	18	1300	67	7360
1×185RM	Al	0,21	17	1300	66	7270
1×240RM	Al	0,16	16,5	1300	67	7480
1×300RM	Al	0,13	15,5	1300	67	7600
1×400RM	Al	0,1	14,5	1400	68	7890
1×500RM	Al	0,08	14	1400	70	8400
1×630RM	Al	0,06	14	1500	74	9390
1×800RM	Al	0,05	14	1600	78	10350
1×1000RM	Al	0,04	14	1700	84	11620
1×1200RMS	Al	0,03	14	1800	91	13250
1×1400RMS	Al	0,03	14	1900	93	14100
1×1600RMS	Al	0,02	14	1900	97	15160
1×1800RMS	Al	0,02	14	2000	101	16410

**NA2X(F)K2Y**

Bezeichnung	Leiter	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1×2000RMS	Al	0,02	14	2100	103	17160
1×2500RMS	Al	0,02	14,5	2200	110	19420
1×3000RMS	Al	0,01	14,5	2400	119	22550