



# NA2X(F)KLD2Y

Hochspannungskabel

Kein Bild verfügbar

## TECHNISCHE DATEN

|                   |                   |
|-------------------|-------------------|
| Isolierung        | Leiter            |
| XLPE              | Aluminum          |
| Mantel            | Nennspannung (kV) |
| PE                | 64/110            |
| Norm              |                   |
| Acc. VDE 0276-632 |                   |

## QUERSCHNITTSDATEN — 64/110 kV

Spannung  
64/110 kV

| Bezeichnung | Leiter | RI [Ohm/km] | Wi [mm] | Rbv [mm] | Ø [mm] | G [kg/km] |
|-------------|--------|-------------|---------|----------|--------|-----------|
| 1×240RM     | Al     | 0,16        | 16,5    | 2100     | 86     | 5510      |
| 1×300RM     | Al     | 0,13        | 15,5    | 2200     | 86     | 5630      |
| 1×400RM     | Al     | 0,1         | 14,5    | 2200     | 87     | 5750      |
| 1×500RM     | Al     | 0,08        | 14      | 2300     | 90     | 6380      |
| 1×630RM     | Al     | 0,06        | 14      | 2400     | 94     | 7000      |
| 1×800RM     | Al     | 0,05        | 14      | 2500     | 98     | 7960      |
| 1×1000RM    | Al     | 0,04        | 14      | 2600     | 103    | 9030      |
| 1×1200RMS   | Al     | 0,03        | 14      | 2800     | 112    | 10450     |
| 1×1400RMS   | Al     | 0,03        | 14      | 2800     | 114    | 11190     |
| 1×1600RMS   | Al     | 0,02        | 14      | 2900     | 118    | 12140     |
| 1×1800RMS   | Al     | 0,02        | 14      | 3100     | 122    | 13220     |
| 1×2000RMS   | Al     | 0,02        | 14      | 3100     | 124    | 13900     |
| 1×2500RMS   | Al     | 0,02        | 14,5    | 3300     | 133    | 15970     |



## NA2X(F)KLD2Y

| Bezeichnung | Leiter | RI [Ohm/km] | Wi [mm] | Rbv [mm] | Ø [mm] | G [kg/km] |
|-------------|--------|-------------|---------|----------|--------|-----------|
| 1×3000RMS   | Al     | 0,01        | 14,5    | 3500     | 141    | 18720     |