



NA2X(F)KLD2Y

Hochspannungskabel

No image available

TECHNICAL DATA

Conductor	Insulation
Aluminum	XLPE
Norm	Rated voltage (kV)
Acc. VDE 0276-632	64/110
Sheath	
PE	

CROSS-SECTION DATA — 64/110 kV

Voltage
64/110 kV

Designation	Cond.	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1×240RM	Al	0.16	16.5	2100	86	5510
1×300RM	Al	0.13	15.5	2200	86	5630
1×400RM	Al	0.1	14.5	2200	87	5750
1×500RM	Al	0.08	14	2300	90	6380
1×630RM	Al	0.06	14	2400	94	7000
1×800RM	Al	0.05	14	2500	98	7960
1×1000RM	Al	0.04	14	2600	103	9030
1×1200RMS	Al	0.03	14	2800	112	10450
1×1400RMS	Al	0.03	14	2800	114	11190
1×1600RMS	Al	0.02	14	2900	118	12140
1×1800RMS	Al	0.02	14	3100	122	13220
1×2000RMS	Al	0.02	14	3100	124	13900
1×2500RMS	Al	0.02	14.5	3300	133	15970



NA2X(F)KLD2Y

Designation	Cond.	RI [Ohm/km]	Wi [mm]	Rbv [mm]	Ø [mm]	G [kg/km]
1×3000RMS	Al	0.01	14.5	3500	141	18720